



① 1x **PL10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **FV3-R (1x) L = 420 mm**



③ incl. **B18**



1 x **K15-Set:**

④ 1x **K15**



⑤ 1x **F11**



⑥ 1x **B16ST (8x40)**



BESTELLDATEN

| | | Art.-Nr. | | |
|--|---------------|----------|--|--|
| Komponenten | | | | |
| 1x PL10 S1 | | | | |
| PL10-100 (FAH min. 550 mm) | 565010 | | | |
| PL10-150 (FAH min. 600 mm) | 565015 | | | |
| PL10-200 (FAH min. 700 mm) | 565020 | | | |
| PL10-300 (FAH min. 1000 mm) | 565030 | | | |
| 1x FV3-R L= 420 mm | | | | |
| FV3-R (1x) FAB min. 450 mm | 515102 | | | |
| 1x Konsolensatz | | | | |
| K15 Set | 517590 | | | |
| Optionales Zubehör | | | | |
| B21-1 Unterlage FV L = 420; FÜ > 10 mm | 515181 | | | |
| B22 Unterlage für B18 auf Glasleiste | 301599 | | | |

Montagevoraussetzungen

| | |
|---------------------------------------|---------------------------|
| Öffnungsrichtung | einwärts |
| Befestigungsmaß Antrieb (Auge – Auge) | 280 ± 7 mm + Hub |
| Platzbedarf FV | min. 38 mm |
| Platzbedarf PL | min. 38 mm |
| Flügelgewicht | max. 30 kg/m ² |
| Flügelbreite (FAB) | 450 – 1300 mm |
| Mindestflügelhöhe (FAH) | vgl. Anbaumaße |
| Bemessungsspannung | 24V DC (19V ... 28V) |
| Abschaltstrom | 0,8 A |
| Bemessungsleistung | 15 W |