



① 2x **PL 10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **FV1** (2x) L= 1200 mm



③ incl. 2x **B18**



2x **K15-Set**

④ 2x **K15**



⑤ 2x **F11**



⑥ 2x **B16ST** (8x40)



⑦ 1x **USKM**



BESTELLDATEN

	Art.-Nr.		
Komponenten			
2x PL10 S1 (Preise je Antrieb)			
PL10-100 (FAH min. 550 mm)	565010		
PL10-150 (FAH min. 600 mm)	565015		
PL10-200 (FAH min. 700 mm)	565020		
PL10-300 (FAH min. 1000 mm)	565030		
1x FV1-R L= 1200 mm			
FV1-R (2x) (FAB min. 1200 mm)	515111		
2x Konsolensatz (Preise je Konsolensatz)			
K15 Set	517590		
1x Kontrollmodul			
USKM	512140		

Optionales Zubehör

B21-2 Unterlage FV L = 1200; FÜ>10 mm	515183		
B22 Unterlage für B18 auf Glasleiste	301599		

Montagevoraussetzungen

Öffnungsrichtung	einwärts
Befestigungsmaß Antrieb (Auge – Auge)	280 ± 7 mm + Hub
Platzbedarf FV	min. 38 mm
Platzbedarf PL	min. 38 mm
Flügelgewicht	max. 30 kg/m ²
Flügelbreite (FAB)	1200 – 2500 mm
Mindestflügelhöhe (FAH)	vgl. Anbaumaße
Bemessungsspannung	24V DC (19V ... 28V)
Abschaltstrom	1,6 A
Bemessungsleistung	30 W