



① 2x **PL10 S1**  
(100 / 150 / 200 / 300 mm)



② 1x **OFV1**



2 x **K15-Set**

③ 2x **K15**



④ 2x **F11**



⑤ 2x **B16ST (8x40)**



⑥ 1x **USKM**



### BESTELLDATEN

		Art.-Nr.		
<b>Komponenten</b>				
<b>2x PL10 S1 (Preise je Antrieb)</b>				
PL10-100 (FAH min. 550 mm)	<b>565010</b>			
PL10-150 (FAH min. 600 mm)	<b>565015</b>			
PL10-200 (FAH min. 700 mm)	<b>565020</b>			
PL10-300 (FAH min. 1000 mm)	<b>565030</b>			
<b>1x OFV1</b>				
OFV1 (FAB min. 450 mm)	<b>513850</b>			
<b>2x Konsolensatz (Preise je Konsolensatz)</b>				
K15 Set	<b>517590</b>			
<b>1x Kontrollmodul</b>				
USKM	<b>512140</b>			

### Montagevoraussetzungen

Öffnungsrichtung	einwärts
Befestigungsmaß Antrieb (Auge – Auge)	280 ± 7 mm + Hub
Platzbedarf OFV (Am Flügelrahmen)	min. 40 mm
Platzbedarf PL (Am Fensterrahmen)	min. 38 mm
Flügelgewicht	max. 30 kg/m <sup>2</sup>
Flügelbreite (FAB)	450 – 1300 mm
Mindestflügelhöhe (FAH)	vgl. Anbaumaße
Bemessungsspannung	24V DC (19V ... 28V)
Abschaltstrom	1,6 A
Bemessungsleistung	30 W