

① 1x **PL6 S1**
(100 / 150 / 200 / 250 mm)



② 1x **FV3** (1x) L = 420 mm




③ inkl. **B18**



1x **K1050-R** altern. **K1050-L**

④ 1x **K97**



⑤ 1x **F11**



⑥ 1x **B16ST** (8x40)



BESTELLDATEN

		Art.-Nr.		
Komponenten				
1x PL6 S1				
PL6-100 (FAB min. 510 mm)	562010			
PL6-150 (FAB min. 600 mm)	562015			
PL6-200 (FAB min. 680 mm)	562020			
PL6-250 (FAB min. 740 mm)	562025			
1x FV3-R L= 420 mm				
FV3-R (1x) (FAB min. 450 mm)	515102			
1x Konsolensatz				
K1050-R Set	307051			
Alternativ 1x				
K1050-L Set	307050			
Optionales Zubehör				
B22 Unterlage für B18 auf Glasleiste	301599			

Montagevoraussetzungen

Öffnungsrichtung	einwärts
Befestigungsmaß Antrieb (Auge – Auge)	280 ± 7 mm + Hub
Platzbedarf FV	min. 38 mm
Platzbedarf PL	min. 20 mm
Flügelgewicht	max. 30 kg/m ²
Flügelbreite (FAB)	450 – 1300 mm
Mindestflügelhöhe (FAH)	vgl. Anbaumaße
Bemessungsspannung	24V DC (19V ... 28V)
Abschaltstrom	0,8 A
Bemessungsleistung	15 W