


① 2x **PL6 S1**
(100 / 150 / 200 / 250 mm)




② 1x **0FV1**



2 **K1050 (1x R + 1x L)**

③ 2x **K97**



④ 2x **F11**



⑤ 2x **B16ST (8x40)**



⑥ 1x **USKM**



BESTELLDATEN

	Art.-Nr.		
Komponenten			
2x PL6 S1 (Preise je Antrieb)			
PL6-100 (FAB min. 510 mm)	562010		
PL6-150 (FAB min. 600 mm)	562015		
PL6-200 (FAB min. 680 mm)	562020		
PL6-250 (FAB min. 740 mm)	562025		
1x 0FV1			
0FV1 (FAH min. 450 mm)	513850		
2x Konsolensatz			
K1050-R Set	307051		
K1050-L Set	307050		
1x Kontrollmodul			
USKM	512140		
Optionales Zubehör			
B22 Unterlage für B18 auf Glasleiste	301599		

Montagevoraussetzungen

Öffnungsrichtung	einwärts
Befestigungsmaß Antrieb (Auge – Auge)	280 ± 7 mm + Hub
Platzbedarf 0FV (Am Flügelrahmen)	min. 40 mm
Platzbedarf PL (Am Fensterrahmen)	min. 20 mm
Flügelgewicht	max. 30 kg/m ²
Flügelbreite (FAB)	1200 – 2500 mm
Mindestflügelhöhe (FAH)	vgl. Anbaumaße
Bemessungsspannung	24V DC (19V ... 28V)
Abschaltstrom	1,6 A
Bemessungsleistung	30 W