



① 1x **PL10 S1**  
(100 / 150 / 200 / 300 mm)



② 1x **FV3-R (1x) L = 420 mm**



③ incl. **B18**



④ 1x **B20-1 (420 mm)**



1 x **K15-Set**

⑤ 1x **K15**



⑥ 1x **F11**



⑦ 1x **B16ST (8x40)**



### BESTELLDATEN

	Art.-Nr.		
<b>Komponenten</b>			
<b>1x PL10 S1</b>			
PL10-100 (FAH min. 550 mm)	<b>565010</b>		
PL10-150 (FAH min. 600 mm)	<b>565015</b>		
PL10-200 (FAH min. 700 mm)	<b>565020</b>		
PL10-300 (FAH min. 1000 mm)	<b>565030</b>		
<b>1x FV3-R L= 420 mm</b>			
FV3-R (1x) ( FAB min. 450 mm)	<b>515102</b>		
<b>1x Anbauplatte</b>			
B20-1 L = 420 mm	<b>515191</b>		
<b>1x Konsolensatz</b>			
K15 Set	<b>517590</b>		
<b>Alternativ je 1x</b>			
1x K37	<b>307500</b>		
1x F11	<b>151400</b>		
1x B16ST	<b>100044</b>		
<b>Optionales Zubehör</b>			
B22 Unterlage für B18 auf Glasleiste	<b>301599</b>		

### Montagevoraussetzungen

Öffnungsrichtung	auswärts
Befestigungsmaß Antrieb (Auge – Auge)	280 ± 7 mm + Hub
Platzbedarf FV	min. 38 mm
Platzbedarf PL	min. 38 mm
Flügelgewicht	max. 30 kg/m <sup>2</sup>
Flügelbreite (FAB)	450 – 1300 mm
Mindestflügelhöhe (FAH)	vgl. Anbaumaße
Bemessungsspannung	24V DC (19V ... 28V)
Abschaltstrom	0,8 A
Bemessungsleistung	15 W