



① 2x **PL10 S1**  
(100 / 150 / 200 / 300 mm)



② 1x **FV1** (2x) L = 1200 mm



③ incl. 2x **B18**



④ 1x **B20-2** (1200 mm)



2 x **K15-Set**

⑤ 2x **K15**



⑥ 2x **F11**



⑦ 2x **B16ST** (8x40)



⑧ 1x **USKM**



### BESTELLDATEN

	Art.-Nr.		
<b>Komponenten</b>			
<b>2x PL10 S1 (Preise je Antrieb)</b>			
PL10-100 (FAH min. 550 mm)	<b>565010</b>		
PL10-150 (FAH min. 600 mm)	<b>565015</b>		
PL10-200 (FAH min. 700 mm)	<b>565020</b>		
PL10-300 (FAH min. 1000 mm)	<b>565030</b>		
<b>1x FV1-R L = 1200 mm</b>			
FV1-R (2x) (FAB min. 1200 mm)	<b>515111</b>		
<b>1x Anbauplatte</b>			
B20-2 L = 1200 mm	<b>515193</b>		
<b>2x Konsolensatz (Preise je Konsolensatz)</b>			
K15 Set	<b>517590</b>		
<b>Alternativ je 2x</b>			
K37	<b>307500</b>		
F11	<b>151400</b>		
B16ST	<b>100044</b>		
<b>1x Kontrollmodul</b>			
USKM	<b>512140</b>		
<b>Optionales Zubehör</b>			
B22 Unterlage für B18 auf Glasleiste	<b>301599</b>		

### Montagevoraussetzungen

Öffnungsrichtung	auswärts
Befestigungsmaß Antrieb (Auge – Auge)	280 ± 7 mm + Hub
Platzbedarf FV	min. 40 mm
Platzbedarf PL	min. 38 mm
Flügelgewicht	max. 30 kg/m <sup>2</sup>
Flügelbreite (FAB)	1200 – 2500 mm
Mindestflügelhöhe (FAH)	vgl. Anbaumaße
Bemessungsspannung	24V DC (19V ... 28V)
Abschaltstrom	1,6 A
Bemessungsleistung	30 W