



- Application: Natural ventilation as single-drive
- Internal load dependent cut-off switch S2 in OPEN / CLOSE direction
- Parallel connection up to 8 drives in one group

### TECHNICAL DATA

<b>U<sub>N</sub></b>	Rated voltage	230V AC (50 Hz)
<b>I<sub>N</sub></b>	Rated current	0,13 A
<b>I<sub>A</sub></b>	Cut-off current	0,2 A
<b>P<sub>N</sub></b>	Rated power	30 W
<b>DC</b>	Duty cycle	5 cycles (ED 30 % - ON: 3 min./OFF: 7 min.)
	Protection rating	IP 32
	Ambient temperature range	-5 °C ... +60°C
<b>F<sub>Z</sub></b>	Pulling force max.	200 N
<b>F<sub>A</sub></b>	Pushing force max.	
		<i>s</i> > 600 mm only for pulling application
<b>F<sub>H</sub></b>	Pullout force	1.800 N (fastening depended)
	Chain	Stainless steel, without protruding rivet heads. Simple connection to casement brackets. Small bending radii allow maximum opening angles of small windows.
	Connecting cable	non-halogen, grey 6 x 0,75 mm <sup>2</sup> , ~ 3 m
<b>v</b>	Speed	10,0 mm/s  10,0 mm/s
<b>s</b>	Stroke	50 – 800 mm
<b>L</b>	Length	see order data
	Sound pressure level	≤ 70 dB (A)

ORDER DATA							
s [mm]	L [mm]	Version	Finish	PU/pcs.	Part.-No.		
200	475	KS2 200 S2 230V R	E6/C-0	1	<b>494920</b>		
		KS2 200 S2 230V L	E6/C-0	1	<b>494720</b>		
300	520	KS2 300 S2 230V R	E6/C-0	1	<b>494930</b>		
		KS2 300 S2 230V L	E6/C-0	1	<b>494730</b>		
400	570	KS2 400 S2 230V R	E6/C-0	1	<b>494940</b>		
		KS2 400 S2 230V L	E6/C-0	1	<b>494740</b>		
500	685	KS2 500 S2 230V R	E6/C-0	1	<b>494950</b>		
		KS2 500 S2 230V L	E6/C-0	1	<b>494750</b>		
600	685	KS2 600 S2 230V R	E6/C-0	1	<b>494960</b>		
		KS2 600 S2 230V L	E6/C-0	1	<b>494760</b>		
800	765	KS2 800 S2 230V R	E6/C-0	1	<b>494980</b>		
		KS2 800 S2 230V L	E6/C-0	1	<b>494780</b>		

OPTIONS							
Special model				PU/pcs.	Part.-No.		
<b>Drive housing painted/powder coated in other RAL colours</b>							
<b>Lump sum for coating</b>					<b>516030</b>		
Specify at order stage:				1 – 20	<b>516004</b>		
				21 – 50	<b>516004</b>		
				51 – 100	<b>516004</b>		
				from 101	<b>516004</b>		
<b>Extra length connecting cable:</b>							
5 m – non-halogen, grey – 6 x 0,75 mm <sup>2</sup>					<b>501164</b>		
10 m – non-halogen, grey – 6 x 0,75 mm <sup>2</sup>					<b>501166</b>		