



① 1x **PL10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **FV3-R (1x) L = 420 mm**



③ incl. **B18**



1 x **K15-Set:**

④ 1x **K15**



⑤ 1x **F11**



⑥ 1x **B16ST (8x40)**



ORDER DATA

	Part.-No.			
Components				
1x PL10 S1				
PL10-100 (FAH min. 550 mm)	565010			
PL10-150 (FAH min. 600 mm)	565015			
PL10-200 (FAH min. 700 mm)	565020			
PL10-300 (FAH min. 1000 mm)	565030			
1x FV3-R L= 420 mm				
FV3-R (1x) FAB min. 450 mm	515102			
1x Frame bracket set				
K15 Set	517590			
Optional accessories				
B21-1 base plate FV L = 420; FÜ>10 mm	515181			
B22 base plate for B18 glazing bead	301599			

Installation requirements

Opening direction	inward
Drive length (eye bolt – eye bolt)	280 ± 7 mm + Stroke
Required mounting space FV (on the window frame profile)	min. 38 mm
Required mounting space PL (on the window frame profile)	min. 38 mm
Weight of the casement	max. 30 kg/m ²
Width of the casement (FAB)	450 – 1300 mm
Min. height of the casement (FAH)	see mounting dimensions
Rated voltage	24V DC (19V ... 28V)
Cut-off current	0,8 A
Rated power	15 W