



① 2x **PL10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **OFV1**



2 x **K15-Set**

③ 2x **K15**



④ 2x **F11**



⑤ 2x **B16ST (8x40)**



⑥ 1x **USKM**



ORDER DATA

		Part.-No.		
Components				
2x PL10 S1 (price per drive)				
PL10-100 (FAH min. 550 mm)		565010		
PL10-150 (FAH min. 600 mm)		565015		
PL10-200 (FAH min. 700 mm)		565020		
PL10-300 (FAH min. 1000 mm)		565030		
1x OFV1				
OFV1 (FAB min. 450 mm)		513850		
2x Frame bracket set (price per frame bracket set)				
K15 Set		517590		
1x Control module				
USKM		512140		

Installation requirements

Opening direction	inward
Drive length (eye bolt – eye bolt)	280 ± 7 mm + Stroke
Required mounting space OFV (on the casemnet profile)	min. 40 mm
Required mounting space PL (On the window frame profile)	min. 38 mm
Weight of the casement	max. 30 kg/m ²
Width of the casement (FAB)	450 – 1300 mm
Min. height of the casement (FAH)	see mounting dimensions
Rated voltage	24V DC (19V ... 28V)
Cut-off current	1,6 A
Rated power	30 W