

① 1x **PL6 S1**
(100 / 150 / 200 / 250 mm)




② 1x **OFV1**



1x **K1050-R** altern. **K1050-L**

③ 1x **K97**



④ 1x **F11**



⑤ 1x **B16ST** (8x40)



ORDER DATA

	Part.-No.		
Components			
1x PL6 S1			
PL6-100 (FAB min. 510 mm)	562010		
PL6-150 (FAB min. 600 mm)	562015		
PL6-200 (FAB min. 680 mm)	562020		
PL6-250 (FAB min. 740 mm)	562025		
1x OFV1			
OFV1 (FAH min. 450 mm)	513850		
1x Frame bracket set			
K1050-R Set	307051		
Alternativ 1x			
K1050-L Set	307050		
Optional accessories			
B22 base plate for B18 glazing bead	301599		

Installation requirements

Opening direction	inward
Drive length (eye bolt – eye bolt)	280 ± 7 mm + Stroke
Required mounting space OFV (on the casemnet profile)	min. 40 mm
Required mounting space PL (on the window frame profile)	min. 20 mm
Weight of the casement	max. 30 kg/m ²
Width of the casement (FAB)	1200 – 2500 mm
Min. height of the casement (FAH)	see mounting dimensions
Rated voltage	24V DC (19V ... 28V)
Cut-off current	1,6 A
Rated power	30 W