










- ① **2x PL6 S1**
(100 / 150 / 200 / 250 mm)

- ② **1x FV1-R (1x) altern. FV1-L (1x)**
L = 420 mm

1x B20-1 (420)

altern.
1x FV1-R (2x)
L = 1200 mm

- ③ incl. **B18**

- 2 K1050 (1x R + 1x L)**
- ④ **2x K97**

- ⑤ **2x F11**

- ⑥ **2x B16ST (8x40)**

- ⑦ **1x USKM**


ORDER DATA

	Part.-No.		
Components			
2x PL6 S1 (price per drive)			
PL6-100 (FAB min. 510 mm)	562010		
PL6-150 (FAB min. 600 mm)	562015		
PL6-200 (FAB min. 680 mm)	562020		
PL6-250 (FAB min. 740 mm)	562025		
1x FV1-R L= 420 mm			
FV1-R (1x) (FAB min. 450 mm)	515103		
1x Mounting plate			
B21-1 base plate FV L = 420; FÜ>10 mm	515181		
B21-2 base plate FV L = 1200; FÜ>10 mm	515183		
2x Frame bracket set			
K1050-R Set	307051		
K1050-L Set	307050		
1x Control module			
USKM	512140		
Optional accessories			
B22 base plate for B18 glazing bead	301599		

Installation requirements

Opening direction	inward
Drive length (eye bolt – eye bolt)	280 ± 7 mm + Stroke
Required mounting space FV (on the window frame profile)	min. 38 mm
Required mounting space PL (on the window frame profile)	min. 20 mm
Weight of the casement	max. 30 kg/m ²
Width of the casement (FAB)	450 – 1300 mm
Min. height of the casement (FAH)	see mounting dimensions
Rated voltage	24V DC (19V ... 28V)
Cut-off current	0,8 A
Rated power	15 W