



① 2x **PL10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **FV1** (2x) L = 1200 mm



③ incl. 2x **B18**



④ 1x **B20-2** (1200 mm)



2 x **K15-Set**

⑤ 2x **K15**



⑥ 2x **F11**



⑦ 2x **B16ST** (8x40)



⑧ 1x **USKM**



ORDER DATA

	Part.-No.		
Components			
2x PL10 S1 (price per drive)			
PL10-100 (FAH min. 550 mm)	565010		
PL10-150 (FAH min. 600 mm)	565015		
PL10-200 (FAH min. 700 mm)	565020		
PL10-300 (FAH min. 1000 mm)	565030		
1x FV1-R L = 1200 mm			
FV1-R (2x) (FAB min. 1200 mm)	515111		
1x Mounting plate			
B20-2 L = 1200 mm	515193		
2x Frame bracket set (price per frame bracket set)			
K15 Set	517590		
Optional 2x			
K37	307500		
F11	151400		
B16ST	100044		
1x Control module			
USKM	512140		
Optional accessories			
B22 base plate for B18 glazing bead	301599		

Installation requirements

Opening direction	outward
Drive length (eye bolt – eye bolt)	280 ± 7 mm + Stroke
Required mounting space FV (on the window frame profile)	min. 40 mm
Required mounting space PL (on the window frame profile)	min. 38 mm
Weight of the casement	max. 30 kg/m ²
Width of the casement (FAB)	1200 – 2500 mm
Min. height of the casement (FAH)	see mounting dimensions
Rated voltage	24V DC (19V ... 28V)
Cut-off current	1,6 A
Rated power	30 W