



## ORDER DATA

|                                     | Part.-No.     |  |  |  |
|-------------------------------------|---------------|--|--|--|
| <b>Components</b>                   |               |  |  |  |
| <b>1x PL10 S1</b>                   |               |  |  |  |
| PL10-100 (FAH min. 550 mm)          | <b>565010</b> |  |  |  |
| PL10-150 (FAH min. 600 mm)          | <b>565015</b> |  |  |  |
| PL10-200 (FAH min. 700 mm)          | <b>565020</b> |  |  |  |
| PL10-300 (FAH min. 1000 mm)         | <b>565030</b> |  |  |  |
| <b>1x FV3-R L= 420 mm</b>           |               |  |  |  |
| FV3-R (1x) ( FAB min. 450 mm)       | <b>515102</b> |  |  |  |
| <b>1x Mounting plate</b>            |               |  |  |  |
| B20-1 L = 420 mm                    | <b>515191</b> |  |  |  |
| <b>1x Frame bracket set</b>         |               |  |  |  |
| K15 Set                             | <b>517590</b> |  |  |  |
| <b>Optional 1x</b>                  |               |  |  |  |
| 1x K37                              | <b>307500</b> |  |  |  |
| 1x F11                              | <b>151400</b> |  |  |  |
| 1x B16ST                            | <b>100044</b> |  |  |  |
| <b>Optional accessories</b>         |               |  |  |  |
| B22 base plate for B18 glazing bead | <b>301599</b> |  |  |  |

## Installation requirements

|  |                           |
|--|---------------------------|
| Opening direction  | outward                   |
| Drive length (eye bolt – eye bolt)                       | 280 ± 7 mm + Stroke       |
| Required mounting space FV (on the window frame profile) | min. 38 mm                |
| Required mounting space PL (on the window frame profile) | min. 38 mm                |
| Weight of the casement                                   | max. 30 kg/m <sup>2</sup> |
| Width of the casement (FAB)                              | 450 – 1300 mm             |
| Min. height of the casement (FAH)                        | see mounting dimensions   |
| Rated voltage  | 24V DC (19V ... 28V)      |
| Cut-off current  | 0,8 A                     |
| Rated power  | 15 W                      |