

ORDER DATA

		Part.-No.			
EMB7300 20 A 0102		683220-0102			
Application:	Compact control unit for smoke and heat exhaust ventilation systems operating with 24 V DC voltage, suitable for staircases.				

**TECHNICAL DATA (Rated values)**

Operating voltage:	230 V AC (195 – 253 V AC, 50/60 Hz)
Max. power consumption:	805 W
Output voltage:	24 V DC (20 – 28 V DC / 0,5 Vpp)
Output current:	20 A
Ambient temperature range:	-5°C ... + 40°C
Protection rating:	IP40 IP54 with alternatively fixing brackets
Housing:	Surface mounting, steel sheet, RAL 7035 (light grey)
Dimensions (WxHxD):	400 x 400 x 200 mm
Connection terminals:	1,5 mm ² / Drives: 6 mm ² (rigid wire)
VdS certification no.:	G 514001

Motherboard: **1 SHEV group / 2 Vent groups**

Feature/Equipment

- Further settings (e.g. maintenance period) only available with extra cost software license
- Cable entry from above / below
- Prepared for **2** maintenance-free backup batteries **2x 12 V / 7 Ah** (Part. Nr. 542000)

10 A**20 A****ACCESSORIES**

Part.-No.		VE			
500001	Wall fixing brackets IP54	4 piece			