







- ① 1x **PL10 S1**  
(100 / 150 / 200 / 300 mm)  

- ② 1x **FV3-R (1x) L = 420 mm**  

- ③ incl. **B18**  

- 1 x **K15-Set:**
- ④ 1x **K15**  

- ⑤ 1x **F11**  

- ⑥ 1x **B16ST (8x40)**  


### 订货信息

		订购号	
套件包括		LZ	PG
<b>1个 PL10 S1</b>			
PL10-100 (FAH 最小550 mm)	565010	●	
PL10-150 (FAH 最小600 mm)	565015	●	
PL10-200 (FAH 最小700 mm)	565020	●	
PL10-300 (FAH 最小 1000 mm)	565030	●	
<b>1x FV3-R L= 420 mm</b>			
FV3-R (1x) FAB 最小 450 mm	515102	●	
<b>1个窗框支架组合</b>			
K15 套件	517590	●	
<b>特殊类型</b>			
套件颜色定制为RAL中的其他颜色	516022	●	net
<b>可选配件</b>			
B21-1 FV垫板 L = 420; FU>10 mm	515181	●	
B22 垫板, 用来支撑B18锁座	301599	●	

### 安装要求

开启方向	内开
开窗器长度 (推头到带眼螺栓)	280 ± 7 mm + Stroke
FV 所需安装空间(装于窗框上)	最小38 mm
PL 所需安装空间(装于窗框上)	最小38 mm
窗扇重量	最大30 kg/m <sup>2</sup>
窗扇宽度(FAB)	450 – 1300 mm
窗扇的最小高度 (FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	0,8 A
额定功率	15 W