



① 2x **PL 10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **FV1** (2x) L= 1200 mm



③ incl. 2x **B18**



2x **K15-Set**

④ 2x **K15**



⑤ 2x **F11**



⑥ 2x **B16ST** (8x40)



⑦ 1x **USKM**



订货信息

		订购号	LZ	PG
套件包括				
2个PL10 S1 (价格为开窗器单价)				
PL10-100 (FAH 最小 550 mm)	565010	●		
PL10-150 (FAH 最小 600 mm)	565015	●		
PL10-200 (FAH 最小 700 mm)	565020	●		
PL10-300 (FAH 最小 1000 mm)	565030	●		
1x FV1-R L= 1200 mm				
FV1-R (2x) (FAB 最小 1200 mm)	515111	●		
2个窗框支架套件 (价格为单价)				
K15 套件	517590	●		
1个控制模块				
USKM模块	512140	●		
特殊类型				
套件定制为RAL中的其他颜色	516022	●	net	
可选配件				
B21-2 FV 垫板, L = 1200; FU>10 mm	515183	●		
B22 垫板, 用来支撑B18锁座	301599	●		

安装要求

开启方向	内开
开窗器长度(推头到带眼螺栓)	280 ± 7 mm + 行程
FV所需安装空间(装于窗框上)	最小38 mm
PL 所需安装空间(装于窗框上)	最小38 mm
窗扇重量	最大30 kg/m ²
窗扇宽度(FAB)	1200 – 2500 mm
窗扇的最小高度(FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	1,6 A
额定功率	30 W