

① 2x **PL10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **OFV1**




2 x **K15-Set**

③ 2x **K15**



④ 2x **F11**



⑤ 2x **B16ST (8x40)**



⑥ 1x **USKM**



订货信息

		订购号			
套件包括		LZ	PG		
2个PL10 S1 (价格为开窗器单价)					
PL10-100 (FAH 最小 550 mm)	565010	●			
PL10-150 (FAH 最小 600 mm)	565015	●			
PL10-200 (FAH 最小 700 mm)	565020	●			
PL10-300 (FAH 最小 1000 mm)	565030	●			
1个OFV1					
OFV1 (FAB 最小450 mm)	513850	●			
2个窗扇支架套件 (价格为单价)					
K15 套件	517590	●			
1个控制模块					
USKM模块	512140	●			
特殊类型					
套件定制为RAL中的其他颜色	516022	●	net		

安装要求

开启方向	内开
开窗器长度 (推头到带眼螺栓)	280 ± 7 mm + 行程
OFV 所需安装空间(装于窗扇上)	最小 40 mm
PL 所需安装空间(装于窗框上)	最小38 mm
窗扇重量	最大 30 kg/m ²
窗扇宽度 (FAB)	450 – 1300 mm
窗扇的最小高度 (FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	1,6 A
额定功率	30 W