

① 1x **PL6 S1**
(100 / 150 / 200 / 250 mm)



② 1x **FV3** (1x) L = 420 mm




③ inkl. **B18**



1x **K1050-R** altern. **K1050-L**

④ 1x **K97**



⑤ 1x **F11**



⑥ 1x **B16ST** (8x40)



订货信息

		订购号	
套件包括		LZ	PG
1个 PL6 S1			
PL6-100 (FAB 最小 510 mm)	562010	●	
PL6-150 (FAB 最小 600 mm)	562015	●	
PL6-200 (FAB 最小 680 mm)	562020	●	
PL6-250 (FAB 最小 740 mm)	562025	●	
1x FV3-R L= 420 mm			
FV3-R (1x) (FAB 最小 450 mm)	515102	●	
1个窗框支架套件			
K1050-R 套件	307051	●	
备选套件 1x			
K1050-L 套件	307050	●	
特殊类型			
套件定制为RAL中的其他颜色	516022	●	net
可选配件			
B22 垫板, 用来支撑B18锁座	301599	●	

安装要求

开启方向	内开
开窗器长度 (推头到带眼螺栓)	280 ± 7 mm + Stroke
FV所需安装空间 (装于窗框上)	最小 38 mm
PL所需安装空间 (装于窗框上)	最小20 mm
窗扇重量	最大30 kg/m ²
窗扇宽度(FAB)	450 – 1300 mm
窗扇的最小高度(FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	0,8 A
额定功率	15 W