

① 1x **PL6 S1**
(100 / 150 / 200 / 250 mm)




② 1x **OFV1**



1x **K1050-R** altern. **K1050-L**

③ 1x **K97**



④ 1x **F11**



⑤ 1x **B16ST** (8x40)



订货信息

		订购号	
套件包括		LZ	PG
1个PL6 S1			
PL6-100 (FAB 最小 510 mm)	562010	●	
PL6-150 (FAB 最小 600 mm)	562015	●	
PL6-200 (FAB 最小 680 mm)	562020	●	
PL6-250 (FAB 最小 740 mm)	562025	●	
1个OFV1			
OFV1 (FAH 最小 450 mm)	513850	●	
1个窗框支架套件			
K1050-R 套件	307051	●	
备用套件 1x			
K1050-L 套件	307050	●	
特殊类型			
套件定制为RAL中的其他颜色	516022	●	net
可选配件			
B22 垫板, 用来支撑B18锁座	301599	●	

安装要求

开启方向	内开
开窗器长度(推头到带眼螺栓)	280 ± 7 mm + 行程
OFV所需安装空间(装于窗扇上)	最小40 mm
PL所需安装空间(装于窗框上)	最小 20 mm
窗扇重量	最大30 kg/m ²
窗扇宽度(FAB)	1200 – 2500 mm
窗扇最小高度(FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	1,6 A
额定功率	30 W