

① 2x **PL6 S1**
(100 / 150 / 200 / 250 mm)




② 1x **OFV1**



2 **K1050 (1x R + 1x L)**

③ 2x **K97**



④ 2x **F11**



⑤ 2x **B16ST (8x40)**



⑥ 1x **USKM**



订货信息

		订购号	
套件包括		LZ	PG
2个PL6 S1 (价格为开窗器单价)			
PL6-100 (FAB 最小510 mm)	562010	●	
PL6-150 (FAB 最小 600 mm)	562015	●	
PL6-200 (FAB 最小680 mm)	562020	●	
PL6-250 (FAB 最小740 mm)	562025	●	
1个OFV1			
OFV1 (FAH 最小 450 mm)	513850	●	
1个安装板			
B20-2 L = 1200 mm	515193	●	
2个窗框支架套件			
K1050-R 套件	307051	●	
K1050-L 套件	307050	●	
1个控制模块			
USKM模块	512140	●	
可选配件			
B22 垫板, 用来支撑B18锁座	301599	●	

安装要求

开启方向	内开
开窗器长度 (推头到带眼螺栓)	280 ± 7 mm + 行程
OFV所需安装空间 (装于窗扇上)	最小40 mm
PL所需安装空间 (装于窗框上)	最小20 mm
窗扇重量	最大30 kg/m ²
窗扇宽度 (FAB)	1200 – 2500 mm
窗扇最小高度 (FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	1,6 A
额定功率	30 W