

RWA1100套件用于外开的上悬窗/下悬窗、平开窗时的安装尺寸																	
套件	窗框支架	开窗器行程	窗户关闭时			安装尺寸 „X“ [mm]	FAH (NSK) (侧边) [mm]	开启角度 [DEG]	开启宽度 [mm]	窗户开启时			窗扇的重量(最大)		窗框上的 安装空间		FAB (HSK) [mm]
			开窗器与竖框 夹角 [DEG]	关闭方向的 分解力 [N]						开启角度 [DEG]	开启方向的 分解力 [N]		PL6 [Kg]	PL10 [Kg]	NSK [mm]	HSK [mm]	
				PL6	PL10						PL6	PL10					
RWA 1100 (*1)	K15	100	19	194	324	400	800	26	365	67	554	923	55	92	40	40	
						500	900	23	360	64	537	896	60	100			
						600	1000	18	320	60	519	865	62	104			
		150	17	171	286	450	900	33	516	75	580	966	58	97	40	40	
						550	1000	28	479	69	559	932	61	103			
						650	1100	24	450	66	549	914	65	108			
		200	15	153	255	500	1000	38	648	79	590	983	59	98	40	40	
						600	1100	32	608	74	577	962	63	105			
						700	1200	28	577	71	566	943	66	110			
						800	1300	25	554	88	600	999	74	123			
		250	13	139	232	900	1400	22	534	66	546	910	70	117	40	40	
						550	1100	41	778	82	595	991	60	99			
						650	1200	36	736	78	586	976	63	106			
						750	1300	31	704	74	576	961	66	111			
						850	1400	28	684	72	571	952	69	116			
		250	12	127	211	950	1500	25	657	69	559	932	71	118	40	40	
						1050	1600	23	638	67	552	921	72	121			
						600	1200	44	907	85	598	996	60	100			
	700					1300	39	861	80	591	985	64	106				
	800					1400	34	828	77	584	973	67	111				
	900					1500	31	799	74	576	960	69	115				
	1000					1600	28	777	72	569	948	71	119				
	K37	100	36	352	586	200	600	42	425	94	599	998	40	67	40	40	
						300	700	28	342	80	591	985	51	84			
						400	800	21	296	73	573	955	57	96			
		150	31	312	520	250	650	42	527	97	595	992	46	76	40	40	
						350	750	35	452	85	598	996	56	93			
						450	850	28	407	78	586	976	62	103			
						550	950	23	376	73	573	955	66	111			
		200	28	279	465	300	750	52	659	99	593	988	47	79	40	40	
						400	850	40	583	88	600	999	56	94			
						500	950	24	390	81	593	988	62	104			
						600	1050	28	499	76	583	972	67	111			
		250	25	253	421	800	1150	24	474	73	573	956	70	116	40	40	
						350	850	55	786	100	591	984	49	81			
						450	950	44	712	90	600	1000	57	95			
550						1050	37	661	84	596	994	62	104				
650						1150	31	622	79	589	982	67	111				
300		23	231	384	750	1250	28	594	76	581	969	70	116	40	40		
					850	1350	25	573	73	573	956	72	120				
	400				1000	58	962	101	589	982	47	79					
	500				1100	47	879	92	600	999	55	91					
	600				1200	40	821	86	598	997	60	100					
	700				1300	35	775	81	593	988	64	106					
	800				1400	31	741	78	587	978	67	112					
900	1500	28	713	75	580	967	70	116									
1000	1600	25	693	73	574	957	72	120									

取决于所使用的电锁 (*2)

(*1) 对于RWA1000 TE双开窗器套件, 开窗器的力和开窗器所能推开的最大窗户宽度相应增高. 对于外开窗, 开窗器轴线的延长线在开启方向离窗户转轴的距离不应小于25mm。以上所注明的安装尺寸适用于型材剖面深度<75 mm的窗户。

(*2) FV1 - 1x = 450 mm
FV1 - 2x = 1200 或 2000 mm
FV1 - 3x = 2000 mm