



① 2x **PL10 S1**
(100 / 150 / 200 / 300 mm)



② 1x **FV1** (2x) L = 1200 mm



③ incl. 2x **B18**



④ 1x **B20-2** (1200 mm)



2 x **K15-Set**

⑤ 2x **K15**



⑥ 2x **F11**



⑦ 2x **B16ST** (8x40)



⑧ 1x **USKM**



订货信息

		订购号	
套件包括		LZ	PG
2个 PL10 S1 (价格为开窗器单价)			
PL10-100 (FAH 最小550 mm)	565010	●	
PL10-150 (FAH 最小600 mm)	565015	●	
PL10-200 (FAH 最小700 mm)	565020	●	
PL10-300 (FAH 最小1000 mm)	565030	●	
1x FV1-R L = 1200 mm			
FV1-R (2x) (FAB 最小1200 mm)	515111	●	
1个安装板			
B20-2 L = 1200 mm	515193	●	
2个 窗框支架套件 (价格单价)			
K15 套件	517590	●	
备选套件 2x			
K37	307500	●	
F11	151400	●	
B16ST	100044	●	
1个控制模块			
USKM模块	512140	●	
特殊类型			
套件定制为RAL中的其他颜色	516022	●	net
可选配件			
B22 垫板, 用来支撑B18锁座	301599	●	

安装要求

开启方向	外开
开窗器长度(推头到带眼螺栓)	280 ± 7 mm + 行程
FV所需安装空间(装于窗框上)	最小 40 mm
PL所需安装空间(装于窗框上)	最小38 mm
窗扇重量	最大 30 kg/m ²
窗扇宽度 (FAB)	1200 – 2500 mm
窗扇的最小高度 (FAH)	取决于安装尺寸
额定电压	24V DC, 2 Vpp
关机电流	1,6 A
额定功率	30 W